

Quick Reference Air Spring Chart

Description	P/N	Customer Order # Sales/Replace Kit P/N	Max Ext. Height	Comp. Height	Max Dia.	Max Load at 100 psi	Design Height	Air Fitting Size (NPTF)	Top Fastener	Bottom Fastener	Mtg. Hole Centers
SLEEVES											
Sleeve 3.0"	58988		8.0	3.6	3.25	410	5.0-6.0	1/8"	3/4" - 16	3/8" - 24	N/A
Sleeve 4.0"	58482	50254	7.0	2.4	4.6	870	4.0-6.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5***	58483	50255	6.25	2.6	5.1	1022	4.0-5.75	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.0"	58287	50269	8.75	3.1	4.6	780	5.5-7.5	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.0***	58430	50208	8.75	3.3	4.6	858	5.0-8.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5***	58387	50260	6.75	2.6	5.1	1076	4.0-6.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5"	58487	50256	6.8	2.4	5.1	1065	4.0-6.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5***	58587	50262	7.75	3.3	5.1	915	4.5-7.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5"	58987	50259	7.75	3.1	5.1	935	4.5-7.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5"	58486		9.75	3.1	5.1	920	6.0-8.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.0"	58586	50272	9.91	3.1	4.6	787	6.0-8.5	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.0"	58786	50202	10.25	3.1	4.6	782	7.5-9.5	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5"	58571	50203	10.25	3.1	5.1	900	6.5-8.5	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 5.0"	58471	50261	10.25	3.1	5.6	965	6.5-8.5	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 5.0"	58688		7.75	3.1	5.6	965	5.0-7.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 6.0"	58341	50200	10.9	4.4	6.8	1680	7.0-8.6	1/8"	M20-2.5	M20-2.5	N/A
BELLOWS											
Bellows 1B-5	58103	50207	5.8	1.8	6.5	1555	3.5-5.0	1/4"	3/8" - 16	3/8" - 16	1.75"
Bellows 1B-6	58407	50352/50252	7.1	1.9	7.0	2210	4.0-6.0	1/8"	3/8" - 24	3/8" - 24	2.75"
Bellows 1B-6**	58736	50284	7.1	2.7	7.0	2210	4.0-6.0	1/8"	3/8" - 24	3/8" - 24	2.75"
Bellows 1B-6 Ultimate**	58740		7.0	2.7	7.0	2210	4.0"-6.0"	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 1B-8	58124	50211	7.3	1.8	9.4	3340	4.0-6.5	1/4"	3/8" - 16	3/8" - 16	2.75"
Bellows 2B-6, Reg.	58439	50351/50251	7.7	2.3	6.5	2025	4.5-6.5	1/8"	3/8" - 24	3/8" - 24	2.75"
Bellows 2B-6, Reg. Ultimate**	58494		8.25	2.7	6.5	2025	4.5"-6.5"	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-6, Ext.	58437	50301/50201	9.1	2.3	7.0	2270	5.0-7.0	1/8"	3/8" - 24	3/8" - 24	2.75"
Bellows 2B-6, Ext.*	58401	50309	9.1	2.3	7.0	2270	5.0-7.0	1/4"	3/8" - 24	3/8" - 24	1.75"
Bellows 2B-6, Ext. **	58491		9.1	2.7	7.0	2270	5.0"-7.0"	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-6, Ext. Ultimate**	58496		9.0	2.7	7.0	2270	5.0"-7.0"	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-6, Crimped on metal, single port	58343		10.5	2.8	7	2030	5.5-7.5	1/2"	3/8"-16	3/8"-16	1.75" - Top Centered - Bottom
Bellows 2B-6, Crimped on metal, dual port	58352		10.5	2.8	7	2030	5.5-7.5	1/2"	3/8"-16	3/8"-16	1.75" - Top Centered - Bottom
Bellows 2B-7, Ext.	58115	50329/50229	9.0	3.3	8.0	2585	6.0-8.0	1/4"	3/8"-16	3/8"-16	2.75"
Bellows 2B-7, Crimped on metal, single port	58616		12.5	2.8	8	3055	6.0-9.0	1/2"	3/8"-16	3/8"-16	2.75"
Bellows 2B-7, Crimped on metal, dual port	58628		12.5	2.8	8	3055	6.0-9.0	1/2"	3/8"-16	3/8"-16	2.75"
Bellows 2B-8	58119		10.3	2.8	8.6	2700	7.0-8.0	1/4"	3/8" - 16	3/8" - 16	2.75"
ROLLING LOBES											
Rolling Lobe, 1R9	58202	58202	11.8	3.2	9.25	4460	6.0-7.5	1/4"	1/2" - 20 3/4" - 16	3/8" - 16	3.38" Top 2.125" Bottom
Rolling Lobe, 1R11	58204	58204	13.0	3.7	11.5	6795	6.0-10.0	1/4"	3/4" - 16 1/2" - 13	1/2" - 13	6.2" Top 2.125" Bottom
TAPERED SLEEVE											
1TS5.0"	58130		9.5"	4.25"	5.4"	1216	6.5-8.5	3/8"	3/8"-24	3/8"-16	2.75" - Top Centered - Bottom

* Replaces Firestone 255C

** Has internal jounce bumper.

NOTE: When ordering replacement bellows for kit numbers 57125 and 57131, the mounting stud, P/N 17210, is not included.